



FOAMSEALR™ GASKET (SHOWN DARK PINK) AT WALL TOP PLATE

JOINTSEALR™ FOAM JOINT TAPE (SHOWN ORANGE)

- 3 1/2" (89mm) BRICK VENEER
- 1" (25mm) AIRSPACE
- 0.8" to 2" (20 to 51mm) FOAMULAR® CODEBORD® SHEATHING: R4 to R10 (RSI 0.70 to 1.76)
- ECOTOUCH® PINK™ FIBERGLAS® INSULATION: R19/R22/R24 (RSI 3.34/3.87/4.23)

JOINTSEALR™ FOAM JOINT TAPE (SHOWN ORANGE)

FOAMSEALR™ GASKET (SHOWN DARK PINK)

FLASHING BEHIND SEALING GASKET (SHOWN DASHED)

FOAMSEALR™ GASKET (SHOWN DARK PINK) BELOW SILL PLATE

DAMP-PROOFING & WATER-PROOFING TO FOUNDATION WALL BELOW GRADE

FOUNDATION DRAINAGE LAYER

CONCRETE FOUNDATION WALL (THICKNESS VARIES)

PROPINK® FIBERGLAS® BLOWN INSULATION: R40-R60 (RSI 7.04-10.57)

6 MIL. POLY VAPOUR/ AIR BARRIER (SHOWN DASHED)

SEAL CEILING 6 MIL. POLY AIR/VAPOUR BARRIER TO UPPER TOP PLATE WITH ACOUSTIC SEALANT (SHOWN RED)

2x6 (38x140mm) STUD WALL

6 MIL. POLY VAPOUR BARRIER (SHOWN DASHED)

GYPSUM BOARD

ECOTOUCH® PINK™ FIBERGLAS® INSULATION: R20/R22/R24 (RSI 3.52/3.87/4.23) w/6 MIL. POLY VAPOUR BARRIER (SHOWN DASHED)

FLOOR JOISTS

2x6 (38x140mm) STUD WALL

GYPSUM BOARD

6 MIL. POLY VAPOUR BARRIER (SHOWN DASHED)

FLOOR JOISTS

ECOTOUCH® PINK™ FIBERGLAS® INSULATION: R20/R22/R24 (RSI 3.52/3.87/4.23) w/6 MIL. POLY VAPOUR BARRIER (SHOWN DASHED)

3" (75mm) FOAMULAR® INSULPINK® EXTRUDED POLYSTYRENE RIGID INSULATION: R15 (RSI 2.64) WITH INSET VERTICAL 1x4 (19x89mm) WOOD FURRING

HORIZONTAL 1x4 (19x89mm) WOOD FURRING PERPENDICULAR TO INSET FURRING (AIRSPACE FOR ELECTRICAL WIRING) 3 ROWS (EQUALLY SPACED)

GYPSUM BOARD

CONCRETE FLOOR SLAB
1" (25mm) FOAMULAR® CODEBORD®: R5 (RSI 0.88) WITH TAPED JOINTS (OPTIONAL 6 MIL. POLY VAPOUR/AIR BARRIER)
GRANULAR BASE

HYBRID:

TYPICAL WALL - BRICK / BRICK
(3" INSULPINK® to Basement)

| TYP. WALL | |
|-----------|-------------|
| DATE: | JUN 14/2013 |
| DRWN BY: | BLR D&D |

