



FOAMSEALR™ GASKET (SHOWN DARK PINK) AT WALL TOP PLATE

JOINTSEALR™ FOAM JOINT TAPE (SHOWN ORANGE)

- PREFINISHED VINYL SIDING
- VERTICAL WOOD STRAPPING
- 0.8" to 2" (20 to 51mm)
- FOAMULAR® CODEBORD® SHEATHING: R4 to R10 (RSI 0.70 to 1.76)
- ECOTOUCH® PINK™ FIBERGLAS® INSULATION: R19/R22/R24 (RSI 3.34/3.87/4.23)

JOINTSEALR™ FOAM JOINT TAPE (SHOWN ORANGE)

FOAMSEALR™ GASKET (SHOWN DARK PINK)

INSTALL FLASHING BEHIND FOAMULAR® CODEBORD® RIGID INSULATION

FOAMSEALR™ GASKET (SHOWN DARK PINK) BELOW SILL PLATE

DAMP-PROOFING & WATER-PROOFING TO FOUNDATION WALL BELOW GRADE

BUILDING PAPER UP AGAINST FOUNDATION WALL FROM TOP OF SLAB TO HEIGHT OF OUTSIDE FINISHED GRADE (SHOWN DASHED)

FOUNDATION DRAINAGE LAYER

CONCRETE FOUNDATION WALL (THICKNESS VARIES)

PROPINK® FIBERGLAS® BLOWN INSULATION: R40-R60 (RSI 7.04-10.57)

6 MIL. POLY VAPOUR/ AIR BARRIER (SHOWN DASHED)

SEAL CEILING 6 MIL. POLY AIR/VAPOUR BARRIER TO UPPER TOP PLATE WITH ACOUSTIC SEALANT (SHOWN RED)

2x6 (38x140mm) STUD WALL

6 MIL. POLY VAPOUR BARRIER (SHOWN DASHED)

GYPSUM BOARD

ECOTOUCH® PINK™ FIBERGLAS® INSULATION: R20/R22/R24 (RSI 3.52/3.87/4.23) w/6 MIL. POLY VAPOUR BARRIER (SHOWN DASHED)

FLOOR JOISTS

2x6 (38x140mm) STUD WALL

GYPSUM BOARD

6 MIL. POLY VAPOUR BARRIER (SHOWN DASHED)

ECOTOUCH® PINK™ FIBERGLAS® INSULATION: R20/R22/R24 (RSI 3.52/3.87/4.23) w/6 MIL. POLY VAPOUR BARRIER (SHOWN DASHED)

FLOOR JOISTS

2x4 or 2x6 (38x89mm or 38x140mm) WOOD STUDS  
 ECOTOUCH® PINK™ FIBERGLAS INSULATION: R20 (RSI 3.52)  
 6 MIL. POLY VAPOUR BARRIER (SHOWN DASHED)  
 GYPSUM BOARD

CONCRETE FLOOR SLAB  
 6 MIL. SEALED POLYETHYLENE AIR/VAPOR BARRIER  
 GRANULAR BASE

HYBRID:

TYPICAL WALL - SIDING / SIDING  
 (Ecotouch® Fiberglas™ Pink Batt Insulation in Basement)

TYP. WALL	
DATE:	JUN 14/2013
DRWN BY:	BLR D&D

